

*Designers & Manufacturers of Drilling & Tapping Solutions*  
**Model VSQ-2500 & VSQ-3250 Vertical Drill Machine**

**Standard Features**

- Rockford Self-Contained, Hydraulic Powered Quill Type Power Unit
- 3 HP Separate Pump Drive Assembly
- 3 to 25 HP Spindle Drive Motor
- HTD Pulleys and Belt
- Enclosed Belt Guard
- Swing Motor Plate Assembly for Easy Adjustment of HTD Drive Belt
- Air Counterbalance Assembly
- Fabricated Steel Base, Riser and Column
- Complete Set of Electrical Controls for Manual and Automatic Operation
- Programmable Controller



**VSQ-2500**

STROKE	0 - 12 INCHES
THRUST	4900 LBS. AT 500 PSI
RAPID APPROACH	110 IPM
MOTOR HORSE POWER	3 TO 20
H.P. TO OPERATE UNIT	3
PUMP RPM	1800
CAPACITY OF RESERVOIR	4 GALLONS
PRESSURE ADJUSTMENT	350 TO 1000 PSI

**VSQ-3250**

STROKE	0 - 12 INCHES
THRUST	8300 LBS. AT 500 PSI
RAPID APPROACH	80 IPM
MOTOR HORSE POWER	3 TO 25
H.P. TO OPERATE UNIT	3
PUMP RPM	1800
CAPACITY OF RESERVOIR	4 GALLONS
PRESSURE ADJUSTMENT	350 TO 1000 PSI

All Machines Can Be Custom Made  
To Meet Your Specifications

